

256K nMOS Dynamic RAM (262144x1) 16PIN 6256

型名	社名	温度範囲 (℃)	スイッチング特性									電 源			入力 [*typ]			出力 [*typ]			リフレ ッシュ Cyc/us	備 考
			TRAC max (ns)	TRCY min (ns)	TCAD min (ns)	TAH min (ns)	TP min (ns)	TWCY min (ns)	TDN min (ns)	TRWC min (ns)	VDD or VCC (V)	IDD max (mA)	IDD STANDBY (1SB/1S82) (mA)	VIL max (V)	VIH min (V)	CI max (pF)	VOL/I VOL max (V/mA)	VOL/I VOL min (V/mA)	VOH/I VOH min (V/mA)	Co max (pF)		
LH21257-20	SHARP	0~70	200	330	35	25	120	330	55	390	4.5~5.5	60	5/-	2.4	0.8	10	0.4/4.2	2.4/5	8	256/4	NIBBLE MODE	
LH21258-10	SHARP	0~70	100	200	20	25	90	200	35	240	4.5~5.5	85	5/-	2.4	0.8	10	0.4/4.2	2.4/5	8	256/4	STATIC COLUMN MODE	
LH21258-12	SHARP	0~70	120	230	25	25	100	230	40	275	4.5~5.5	80	5/-	2.4	0.8	10	0.4/4.2	2.4/5	8	256/4	STATIC COLUMN MODE	
LH21258-15	SHARP	0~70	150	260	30	25	100	260	45	310	4.5~5.5	70	5/-	2.4	0.8	10	0.4/4.2	2.4/5	8	256/4	STATIC COLUMN MODE	
LH21258-20	SHARP	0~70	200	330	35	25	120	330	55	390	4.5~5.5	60	5/-	2.4	0.8	10	0.4/4.2	2.4/5	8	256/4	STATIC COLUMN MODE	
MSM4256A-10	MITSUBISHI	0~70	100	190	15	15	80	190	20	220	4.5~5.5	65	4.5/-	0.8	2.4	5	0.4/4.2	2.4/5	7			
MSM4256A-12	MITSUBISHI	0~70	120	220	20	20	90	220	25	255	4.5~5.5	60	4.5/-	0.8	2.4	5	0.4/4.2	2.4/5	7			
MSM4256A-15	MITSUBISHI	0~70	150	260	25	25	100	260	30	295	4.5~5.5	55	4.5/-	0.8	2.4	5	0.4/4.2	2.4/5	7			
MSM4256A-85	MITSUBISHI	0~70	85	160	15	15	65	160	15	185	4.5~5.5	70	4.5/-	0.8	2.4	5	0.4/4.2	2.4/5	7			
MSM4256P-12	MITSUBISHI	0~70	120	230	30	20	100	230	30	260	4.5~5.5	65	4.5/-	0.8	2.4	5	0.4/4.2	2.4/5	10	256/4		
MSM4256P-15	MITSUBISHI	0~70	150	260	30	25	100	260	35	295	4.5~5.5	60	4.5/-	0.8	2.4	5	0.4/4.2	2.4/5	10	256/4		
MSM4256P-20	MITSUBISHI	0~70	200	330	40	35	120	330	40	370	4.5~5.5	50	4.5/-	0.8	2.4	5	0.4/4.2	2.4/5	10	256/4		
MSM4256P/1/L-10	MITSUBISHI	0~70	100	200	15	15	100	200	25	235	4.5~5.5	70	4.5/-	0.8	2.4	10	0.4/4.2	2.4/5	7	256/4	PAGE MODE	
MSM4256S-12	MITSUBISHI	0~70	120	230	30	20	100	230	30	260	4.5~5.5	65	4/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4		
MSM4256S-15	MITSUBISHI	0~70	150	260	30	25	100	260	35	295	4.5~5.5	60	4/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4		
MSM4256S-20	MITSUBISHI	0~70	200	330	40	35	120	330	40	370	4.5~5.5	50	4/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4		
MSM4257A-10	MITSUBISHI	0~70	100	190	15	15	80	190	20	220	4.5~5.5	65	4.5/-	0.8	2.4	5	0.4/4.2	2.4/5	7			
MSM4257A-12	MITSUBISHI	0~70	120	220	20	20	90	220	25	255	4.5~5.5	60	4.5/-	0.8	2.4	5	0.4/4.2	2.4/5	7			
MSM4257A-15	MITSUBISHI	0~70	150	260	25	25	100	260	30	295	4.5~5.5	55	4.5/-	0.8	2.4	5	0.4/4.2	2.4/5	7			
MSM4257A-85	MITSUBISHI	0~70	85	160	15	15	65	160	15	185	4.5~5.5	70	4.5/-	0.8	2.4	5	0.4/4.2	2.4/5	7			
MSM4257P-12	MITSUBISHI	0~70	120	230	20	20	100	230	30	260	4.5~5.5	65	4.5/-	0.8	2.4	5	0.4/4.2	2.4/5	10	256/4		
MSM4257P-15	MITSUBISHI	0~70	150	260	25	25	100	260	35	295	4.5~5.5	60	4.5/-	0.8	2.4	5	0.4/4.2	2.4/5	10	256/4		
MSM4257P-20	MITSUBISHI	0~70	200	330	30	35	120	330	40	370	4.5~5.5	50	4.5/-	0.8	2.4	5	0.4/4.2	2.4/5	10	256/4		
MSM4257P/1/L-10	MITSUBISHI	0~70	100	200	15	15	90	200	25	225	4.5~5.5	70	4.5/-	0.8	2.4	10	0.4/4.2	2.4/5	7	256/4	NIBBLE MODE	
MSM4257S-12	MITSUBISHI	0~70	120	230	30	20	100	230	30	260	4.5~5.5	65	4/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4		
MSM4257S-15	MITSUBISHI	0~70	150	260	30	25	100	260	35	295	4.5~5.5	60	4/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4		
MSM4257S-20	MITSUBISHI	0~70	200	330	40	35	120	330	40	370	4.5~5.5	50	4/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4		
MB81256-10	FUJITSU	0~70	100	200	20	15	85	200	15	200	4.5~5.5	70	4.5/-	0.8	2.4	7	0.4/4.2	2.4/5	7			
MB81256-12	FUJITSU	0~70	120	220	22	20	90	220	20	220	4.5~5.5	65	4.5/-	0.8	2.4	7	0.4/4.2	2.4/5	7			
MB81256-15	FUJITSU	0~70	150	260	25	25	100	260	25	260	4.5~5.5	57	4.5/-	0.8	2.4	7	0.4/4.2	2.4/5	7			
MB81256-80	FUJITSU	0~70	80	175	20	15	80	180		180	4.5~5.5	65	4/-	0.8	2.4	10	0.4/4.2	2.4/5	7		PAGE MODE	
MB81257-10	FUJITSU	0~70	100	200	20	15	85	200	15	200	4.5~5.5	70	4.5/-	0.8	2.4	7	0.4/4.2	2.4/5	7			
MB81257-12	FUJITSU	0~70	120	220	22	20	90	220	20	220	4.5~5.5	65	4.5/-	0.8	2.4	7	0.4/4.2	2.4/5	7			
MB81257-15	FUJITSU	0~70	150	260	25	25	100	260	25	260	4.5~5.5	57	4.5/-	0.8	2.4	7	0.4/4.2	2.4/5	7			
MB81257-80	FUJITSU	0~70	80	175	20	15	80	180		180	4.5~5.5	65	4/-	0.8	2.4	10	0.4/4.2	2.4/5	7		NIBBLE MODE	
MC6256-10	MOTOROLA		100								4.5~5.5	70	4/-							256/4		
MC6256-12	MOTOROLA		120								4.5~5.5	70	4/-							256/4		
MC6256-15	MOTOROLA		150								4.5~5.5	70	4/-							256/4		
MC6257B-10	MOTOROLA	0~70	100	190	25	20	80	190	20	200	4.5~5.5	80	5/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4	NIBBLE MODE	
MC6257B-12	MOTOROLA	0~70	120	220	25	25	90	220	25	240	4.5~5.5	72	5/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4	NIBBLE MODE	
MC6257B-15	MOTOROLA	0~70	150	260	25	30	100	260	30	285	4.5~5.5	65	5/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4	NIBBLE MODE	
MN41256-12	MATSUSHITA	0~70	120	220	25	20	90	220	25	225	4.5~5.5	70	5/-	0.8	2.4	8	0.4/4.2	2.4/5	7	256/4		