

64K CMOS Static RAM (8192×8) 28PIN 6264

型名	社名	温度範囲 (℃)	スイッチング特性										電源			入力 [*typ]			出力 [*typ]			備考
			TAAC max (ns)	TCAC max (ns)	TOE max (ns)	T0H min (ns)	T0D max (ns)	TWP min (ns)	TDS min (ns)	TDH min (ns)	TWD min (ns)	TWR max (ns)	VID or VCC (V)	IDD max (mA)	ID3 (1.5B/1.5E) (mA)	STANDBY (mA)	VIL max (V)	VIH min (V)	CI max (pF)	VOL/1 VOL max (V/mA)	VOH/1 VOH min (V/mA)	
CL3664R/RM/RS-15	SANYO	0~70	150	150	5	15	50	90	75	0	0	10	4.5~5.5	35		1/3	0.8	2.2	6*	0.4/2.0	2.4/1.0	6*
CL3664R/RM/RS-12	SANYO	0~70	120	120	5	15	40	80	65	0	0	10	4.5~5.5	35		0.1/3	0.8	2.2	6*	0.4/2.0	2.4/1.0	6*
CL3664R/RM/RS-15	SANYO	0~70	150	150	5	15	50	90	75	0	0	10	4.5~5.5	35		0.1/3	0.8	2.2	6*	0.4/2.0	2.4/1.0	6*
CXK5863P-25	SONY	0~70	25		15	5	15	20	12	0	0		4.5~5.5	90		25/0.01	0.8	2.2	7	0.4/8	2.4/4	10
CXK5863P-30	SONY	0~70	30		15	5	15	20	12	0	0		4.5~5.5	90		25/0.01	0.8	2.2	7	0.4/8	2.4/4	10
CXK5863P-35	SONY	0~70	35		20	5	20	25	15	0	0		4.5~5.5	90		25/0.01	0.8	2.2	7	0.4/8	2.4/4	10
CXK5864-M-12	SONY		120		60	10	45	70		0	15		4.5~5.5	30		5/-	0.8	2.2	7	0.4/2.1	2.4/1	7
CXK5864-M-15	SONY		150		70	10	50	90		0	10		4.5~5.5	30		5/-	0.8	2.2	7	0.4/2.1	2.4/1	7
CXK5864M-10L	SONY		100		50	10	35	60		0	20		4.5~5.5	45		3/-	0.8	2.2	7	0.4/8	2.4/3.2	7
CXK5864M-70L	SONY		70		35	10	30	50		0	15		4.5~5.5	45		3/-	0.8	2.2	7	0.4/8	2.4/3.2	7
CXK5864AP-10L	SONY		100		50	10	35	60		0	20		4.5~5.5	45		3/-	0.8	2.2	7	0.4/8	2.4/3.2	7
CXK5864AP-70L	SONY		70		35	10	30	50		0	15		4.5~5.5	45		3/-	0.8	2.2	7	0.4/8	2.4/3.2	7
CXK5864ASP-10L	SONY	0~70	100		50	10	35	60	35	0	0		4.5~5.5	50		3/0.06	0.6	2.4	7	0.4/8	2.4/4	7
CXK5864ASP-70L	SONY	0~70	70		35	10	30	40	30	0	0		4.5~5.5	50		3/0.06	0.6	2.4	7	0.4/8	2.4/4	7
CXK5864M-12L	SONY		120		60	10	45	70		0	15		4.5~5.5	25		2/-	0.8	2.2	7	0.4/2.1	2.4/1	7
CXK5864M-15L	SONY		150		70	10	50	90		0	10		4.5~5.5	25		2/-	0.8	2.2	7	0.4/2.1	2.4/1	7
CXK5864P-10	SONY	0~70	100		50	10	40	60	40	0	10		4.5~5.5	90		5/2	0.6	2.4	7	0.4/2.1	2.4/1	10
CXK5864P-10L	SONY	0~70	100		50	10	40	60	40	0	10		4.5~5.5	60		3/0.2	0.8	2.2	7	0.4/2.1	2.4/1	10
CXK5864P-12	SONY	0~70	120		60	10	45	70	50	0	10		4.5~5.5	90		5/2	0.6	2.4	7	0.4/2.1	2.4/1	10
CXK5864P-12L	SONY	0~70	120		60	10	45	70	50	0	10		4.5~5.5	60		3/0.2	0.8	2.2	7	0.4/2.1	2.4/1	10
CXK5864P-15	SONY	0~70	150		70	10	50	90	60	0	10		4.5~5.5	90		5/2	0.6	2.4	7	0.4/2.1	2.4/1	10
CXK5864P-15L	SONY	0~70	150		70	10	50	90	60	0	10		4.5~5.5	60		3/0.2	0.8	2.2	7	0.4/2.1	2.4/1	10
CXK5864PN-10	SONY	0~70	100		50	10	40	60	40	0	0		4.5~5.5	90		5/2	0.8	2.2	7	0.4/2.1	2.4/1	10
CXK5864PN-10L	SONY	0~70	100		50	10	40	60	40	0	0		4.5~5.5	60		3/0.1	0.8	2.2	7	0.4/2.1	2.4/1	10
CXK5864PN-12	SONY	0~70	120		60	10	45	70	50	0	0		4.5~5.5	90		5/2	0.8	2.2	7	0.4/2.1	2.4/1	10
CXK5864PN-12L	SONY	0~70	120		60	10	45	70	50	0	0		4.5~5.5	60		3/0.1	0.8	2.2	7	0.4/2.1	2.4/1	10
CXK5864PN-15	SONY	0~70	150		70	10	50	90	60	0	0		4.5~5.5	90		5/2	0.8	2.2	7	0.4/2.1	2.4/1	10
CXK5864PN-15L	SONY	0~70	150		70	10	50	90	60	0	0		4.5~5.5	60		3/0.1	0.8	2.2	7	0.4/2.1	2.4/1	10
CXK5865M-45	SONY		45		20	5	25	30		0	10		4.5~5.5	80		25/-	0.8	2.2	7	0.4/8	2.4/4	7
CXK5865M-45L	SONY		45		20	5	25	30		0	10		4.5~5.5	80		25/-	0.8	2.2	7	0.4/8	2.4/4	7
CXK5865M-55	SONY		55		25	5	25	35		0	15		4.5~5.5	80		25/-	0.8	2.2	7	0.4/8	2.4/4	7
CXK5865M-55L	SONY		55		25	5	25	35		0	15		4.5~5.5	80		25/-	0.8	2.2	7	0.4/8	2.4/4	7
CXK5865P-45	SONY		45		20	5	25	30		0	10		4.5~5.5	80		25/-	0.8	2.2	7	0.4/8	2.4/4	7
CXK5865P-45L	SONY		45		20	5	25	30		0	10		4.5~5.5	80		25/-	0.8	2.2	7	0.4/8	2.4/4	7
CXK5865P-55	SONY		55		25	5	25	35		0	15		4.5~5.5	80		25/-	0.8	2.2	7	0.4/8	2.4/4	7
CXK5865P-55L	SONY		55		25	5	25	35		0	15		4.5~5.5	80		25/-	0.8	2.2	7	0.4/8	2.4/4	7
CY7C185-12PC/VC/DC/LC	CYPRESS	0~70	12	12	10		8	10	10	0	0	0	4.5~5.5	125			0.8	2.2	5	0.4/8.0	2.4/4.0	7
CY7C186-12PC/VC/DC/LC	CYPRESS	0~70	12	12	10		8	10	10	0	0	0	4.5~5.5	125			0.8	2.2	5	0.4/8.0	2.4/4.0	7
CY7C186-25	CYPRESS	0~70	25	25	15	3	15	20	10	0	0	0	4.5~5.5	100		20/20	0.8	2.2	5	0.4/8	2.4/4	7
CY7C186-35	CYPRESS	0~70	35	35	20	3	15	20	15	0	0	0	4.5~5.5	100		20/20	0.8	2.2	5	0.4/8	2.4/4	7
CY7C186-45	CYPRESS	0~70	45	45	20	3	20	25	20	0	0	0	4.5~5.5	100		20/20	0.8	2.2	5	0.4/8	2.4/4	7
CY7C186-55	CYPRESS	0~70	55	55	25	3	25	30	25	0	0	0	4.5~5.5	80		20/20	0.8	2.2	5	0.4/8	2.4/4	7